ACCESSORIES

i-com Series UPS Accessories

Model: RMP-X1

UPS remote monitoring panel

- Touchscreen TFT display
- RS485 input port (for long distance)
- RS232 input port
- RS232 output port + dry contact port
- Emergency stop input
- Functional desktop and wall-mount design

Model: US-4 & US-8

UPS multiserver shutdown unit
(Dry contact multiplexer)

- RS232 input port
- RS232 output
- 4 or 8 multiplexed dry contact output

Model: ML100

Serial port multiplexer for UPS and STS

- RS232 input port
- 2 x DB9 type socket RS232 outputs
- External or internal

Model: ML200

Internal Serial port multiplexer for UPS and STS

- RS232 input port
- DB9 type socket RS232 output
- RJ45 Ethernet output (TCP/IP)

Tescom®

ACCESSORIES

Model: SNMP

External SNMP adaptor for UPS

- WEB based monitoring & management
- SNMP management
- Multi server shutdown
- Multi UPS monitoring

Model: RSX24

External RS232 to RS485 converter for UPS and STS

- For long distance communication
- Bi-directional operation
- 4 wire RS485 output (Half & full duplex)

Model: RS-NET

External RS232 to TCP/IP converter for UPS and STS

- Monitoring & management over TCP/IP

ACCESSORIES

i-com Series UPS Accessories

Model: MDX2

External MODBUS over RS485 adaptor for UPS and STS

- For SCADA and BMS connection
- MODBUS RTU protocol
- 2 wire RS485 output
- 8 bit hardware addressable

Model: MDX-NET

External MODBUS over TCP/IP adaptor for UPS and STS

- For SCADA and BMS connection
- MODBUS TCP protocol
- RJ45 Ethernet output
- 8 bit hardware addressable

Model: GM-1

External GSM modem for UPS

- For SMS option
- SNMP compability
- Control via AT commands
- Configuration by the SNMP web interface
- Push-push SIM card installation

Tescom®

ACCESSORIES

Model: GM-2

External GSM / GPRS modem for UPS

• SMS option
• Monitoring & management via GPRS and SMS
• Directly UPS connection
• Smart modem
• Push-push SIM card installation
• Easy configuration by the Utility PC software

Model: GM-3

External GSM / GPRS modem for UPS
with Internal battery unit

• SMS option
• Monitoring & management via GPRS and SMS
• Directly UPS connection
• Smart modem
• Push-push SIM card installation
• Easy configuration by the Utility PC software
• Uninterruptible communication with internal battery

Model: GMB1

External Battery Unit for GM-2 Modem

• This unit is the external battery bank for GM-2 modem.